



TPDS40W - WiFi : Smart 3-Phase Motor Starter with Water Level Controller

The TPDS40W-WiFi is a cutting-edge, fully automatic water level controller designed for three-phase motors. Integrated with the "Ktronics Tank Monitor" Android app, it allows users to monitor and control their water pumps remotely via Wi-Fi. Multiple users can install the app to access real-time water levels and motor status, enhancing accessibility and control.



Key Features:

- Remote Monitoring & Control: Monitor tank water levels and control the motor remotely through the "Ktronics Tank Monitor" Android app, accessible from anywhere with an internet connection.
- Flexible Sensor Connectivity: Supports both wired local sensors and remote sensors connected through a cloud server, making it ideal for tanks located far from the motor.
- Motor Protection System: Safeguards three-phase motors against overload, dry run, and phase loss, preventing potential damage and ensuring longevity.
- Cyclie Timer: Features a built-in cyclic timer that allows users to set periodic motor operation intervals, optimizing water distribution.
- Current Monitoring: Continuously monitors the current drawn by the motor. Users can adjust low and high current settings to prevent damage. The system turns off the motor in case of overcurrent, undercurrent (dry run), or phase loss.
- Tripping Alerts: Displays the reason for motor shutdown along with the tripping current, aiding in quick diagnostics.
- Off Timer: Includes an off timer that automatically turns off the motor after a set duration, conserving energy and preventing overflows.
- Water Level Sensors: Additional sensors can be connected to overhead or underground tanks to automatically turn off the motor when the tank is full.



Specifications:

- Load Capacity: Up to 40A, 415V AC
- Motor Compatibility: Suitable for motors up to 7.5 HP
- Input/Output: RYB Input & RYB Output
- **Protection Features:** High & low voltage protection, overload protection, short circuit protection
- Display: Digital volt and ampere meters
- Control Modes: Auto and manual modes with bypass option
- Timers: Cyclic timer, on delay and off delay timers, off timer
- Indications: Motor on indication, RYB phase indication, auto and bypass switch indications

Installation & Compatibility:

The TPDS40W-WiFi is designed to be attached to existing motor starters. It allows the motor load to pass through the provided current transformer (CT) for accurate current sensing. This setup ensures comprehensive monitoring and protection of the motor.

Ideal Applications:

- **Residential Use:** Ensures efficient water management in homes, preventing overflow and dry run scenarios.
- Commercial Establishments: Suitable for hotels, resorts, and offices, providing reliable water supply management.
- Industrial Applications: Facilitates automated water distribution in factories and large facilities, optimizing resource usage.

✓ Settings
Alerts
Manage notifications, audio alerta, and ^
Voice Alert
Vibration Alert
Vibration Alert
Notifications Alert
Alert Events
Mater truggers based on water levels, ^
On 0% Level
On 20% Level
On 40% Level
On 80% Level
On 80% Level
On 80% Level
On 80% Level
On 100% Level
On 100% Level



With its comprehensive features and user-friendly interface, the TPDS40W-WiFi offers an efficient solution for modern water level management and motor protection.